

ITEM NUMBER: C-861

IDENTITY (As Used On Label and List): ELKY PRO BEGONE STAIN REMOVER

EMERGENCY MEDICAL Telephone# 1-800-424-9300 (24 Hrs)

Outside of the U.S.A. Call 703-527-3887

PRODUCT HAZARD RATINGS (NFPA): Health = 1, Fire = 2, Reactivity = 0, Protective Equipment = B
(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

SECTION I

HESCO Inc.
Niles, IL 60714

TELEPHONE NUMBER FOR INFORMATION: 1-800-822-7467

DATE PRINTED: 12/12/03

NAME OF PREPARER: Ron Cepa

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names	EXPOSURE LIMITS (LD50-ORAL RAT)	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
Trichloroethylene (CAS#79-01-6)	>4.9 g/kg	YES	50 ppm	50 ppm	45-55
Perchloroethylene (CAS#127-18-4)	3.98/4.68g/kg	YES	50	25	45-55
Carbon Dioxide (CAS#124-38-9)	NA	--	5,000	10,000	<5.0

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.

Components Listed As A Suspected Carcinogen: The International Agency for Research on Cancer (IARC) has determined that Trichloroethylene and Perchloroethylene may cause cancer in humans based on animal data.

This product contains chemicals known to the State of California to cause cancer.

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 132 @130F Specific Gravity (H2O=1): >1.0
 Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1
 Appearance and Odor: Forceful stream with ether-like odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: This product is considered to be non flammable as described in 16CFR 1500.45.

Flammable Limits - % Volume In Air (Trichloroethylene): LEL: 7.8% UEL: 10.5%*

Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.

Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.

Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.

Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure. *Vapors concentrated in a confined or poorly ventilated area can be ignited upon contact with a high energy spark, flame or high intensity source of heat.

SECTION V - REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: NA

Incompatibility (Materials to Avoid): Oxidizing agents and aluminum equipment

Thermal Decomposition Products: oxides of carbon, hydrogen chloride, phosgen and chlorine

Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry - Inhalation: X Eyes: X Skin: X Ingestion: X

Signs and Symptoms of Exposure: Prolonged or repeated contact of liquid can cause irritation, defatting of skin, and dermatitis. Exposure to high vapor concentrations can cause central nervous system depression with symptoms of headache, dizziness, stupor, loss of consciousness or death depending on concentration and duration of exposure.

Ingestion or vomiting can result in aspiration into the lungs which can cause chemical pneumonia and systemic effects.

Medical Conditions Generally Aggravated by Exposure: Acute and chronic liver and kidney disease, rhythm disorders of the heart and neuritis can be aggravated by exposure to this product.

Emergency and First Aid Procedures: Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention if irritation persists. Skin Contact: Remove contaminated clothing. Flush skin with water, follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention. Ingestion: Get medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Releases or Spilled: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material.

Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.

Handling And Storing: Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 130F (54C). Store as Level 1 Aerosol (NFPA 30B).

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

SECTION VIII - EMPLOYEE PROTECTION

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.

Ventilation: Local exhaust is adequate under normal conditions, mechanical ventilation is optional.

Protective Gloves: Chemical resistant gloves*.

Eye Protection: Chemical safety glasses are recommended*.

Other Protective Clothing or Equipment: Wear impervious clothing to prevent skin contact.

Work/Hygienic Practices: Ensure strict sanitary conditions are conformed to when working around chemicals.

Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

SECTION IX - OTHER REGULATORY CONTROLS

Governmental Listings: Ingredients of this product are listed on the EPA/TSCA Inventory of Chemical Substances.

SECTION X - TRANSPORTATION REQUIREMENTS (D.O.T. CLASSIFICATION)

Shipping Name: Consumer Commodity Hazard Class: ORM-D

NG-- Negligible NA-- Not Applicable NE-- Not Established UN-- Unavailable ND-- Not Determined

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.

As of: September 29, 1998